

REATEC®
SWISS MADE

Temperature Indicators

Advantages

Easy to use, even in inaccessible places.

Instructions

Apply to a clean surface, after removing the protective paper from the back.

If the temperature reaches an indicated value, the corresponding element will show an irreversible colour change to black. Tolerance $\pm 1\%$ of the indicated temperature. (Warming up $2^\circ\text{C}/\text{min.}$) Reaction time is about 2 seconds.

Precautions

Keep dry and cool.

Standard REATEC® should be used only under dry conditions, free of oil, grease, water, detergents etc. if contact with such materials is necessary, use REATEC® P indicators.

Over a long period near to the temperature indicated, an element may turn grey. For a permanent control, the strips should be changed from time to time.

Temperature ranges

Strips for the following ranges:

No. 001	37.8 - 77 °C
No. 002	82 -132 °C
No. 003	138 -188 °C
No. 004	193 -254 °C
No. 01A	54,4 -104 °C
No. 02A	110 -160 °C
No. 03A	166 -216 °C
No. 041	199 -260 °C
No. 062	62 - 80 °C
No. 082	82 -100 °C
No. 102	102 -120 °C
No. 214	214 -232 °C
No. 042	224 -264 °C

REATEC® standard self-adhesive
REATEC® P self-adhesive
REATEC® P are not available for the ranges
062, 082, 102, 214 and 042

Do not eat and do not bring in contact with foodstuffs and beverages. The indicators are manufactured with the greatest care. However, no responsibility is taken for their application. Defective indicators will be replaced free of charge. Any other indemnification is not applicable.

Manufactured in Switzerland by
REATEC AG CH-8600 Dübendorf
Telefon +41 (44) 821 71 11
Telefax +41 (44) 821 71 03
www.reatec.ch info@reatec.ch