

## ISO Flow Cups

**ISO Flow Cups** produced by our company are in accordance with International Standard ISO 2431, DIN 53224, EN 535; ASTM D 5125 《Paints and varnishes-Determination of flow time by Use of Flow Cups (Fourth edition)》. They are made of high quality aluminum and feature stainless steel nozzle inserts (specification dependent). They are mirror polished & smooth finished ( $Ra \leq 0.5\mu m$ ) for high efflux accuracy and easy maintenance. ISO Flow Cups are applicable to Determine the flow time of Newtonian and near Newtonian fluids.

### Main Technical Parameters:

- ★ Material: Anodized Aluminum
- ★ Weight: 0.38Kg
- ★ Come with calibration certificate



### ◆ Details of each ISO Cups

Details/ISO Cup	ISO No.3	ISO No.4	ISO No.5	ISO No.6	ISO No.8
Orifice $\phi$ (mm)	3.0	4.0	5.0	6.0	8.0
Suitable Flow Time (sec)	30-100	30-100	30-100	30-100	30-100
Measurement Range (cSt)	7-42	34-135	91-326	188-684	600-2000
Ordering Information	BGD 128/3	BGD 128/4	BGD 128/5	BGD 128/6	BGD 128/8



Operating Steps